



Angloco

Water / Foam Tender – 3100



OUTLINE SPECIFICATION

Chassis & Crew Cab

Scania P410CB4X4HHZ 4x4 rigid chassis.
Engine: 410 hp (302 kW).
Gearbox: Automatic.
GVW: 19,000 kg.
Scania CP28 crew cab with air conditioning.
Seating for 6 occupants (driver plus five).
Crew seats with integrated SCBA stowage.

Fire Engineering

Water Tank 2,900 litre capacity.

Foam Tank 230 litre capacity.

Water Pump Aluminium multi-pressure centrifugal pump, nominally rated at 2,500 litre/min at 7 bar. High pressure output for the hose reels. Central suction connection. Four rear-facing screw-down delivery valves. Automatic primer.

Hose Reels Two high pressure hose reels, each with 54 m of 25 mm bore hose and jet/spray branch pipe.

Foam System Automatic round-the-pump proportioning.

Bodywork

Heavy duty aluminium alloy construction. Three lockers each side, plus rear pump compartment, enclosed by aluminium roller shutters. Custom stowage for fire fighting and rescue equipment including heavy duty slide-out trays. De-mount gantries for 10.5 m extension ladder and roof ladder.

Equipment / Accessories

LED emergency warning light bar. Emergency warning siren and PA system. Two-tone emergency warning horns. Four lengths of suction hose with strainer. 14 lengths of delivery hose. Four jet/spray water branch pipes. Four foam branch pipes. Collecting head. Dividing breeching. 10.5 m extension ladder. Roof ladder. Portable generator. PPV fan. Floodlighting. Mains powered battery charger with auto-eject connector.