



# Angloco

## Water / Foam Tender – 4800



### OUTLINE SPECIFICATION

**Chassis & Cab** Scania P310CB4x2MSZ 4x2 rigid chassis.  
Engine: 310 hp (228 kW).  
Gearbox: Automatic.  
GVW: 19,500 kg.  
Scania CP28 four-door crew cab.  
Seating for 6 occupants (driver plus five).

### Fire Engineering

**Water Tank** 4,550 litre capacity, GRP construction.

**Foam Tank** 250 litre capacity.

**Water Pump** Multi-pressure bronze/gunmetal centrifugal pump, rated at 2,500 litres/min at 7 bar.  
Discharge to four delivery outlets, and high pressure discharge for two hose reels.

**Foam System** Automatic round-the-pump foam proportioning system for 3% or 6% selectable mixing ratio.

**Hose Reels** Two powered rewind high pressure hose reels, 54 m x 25 mm hose, jet/spray branch pipe.

**Bodywork** Heavy duty light weight aluminium construction with side lockers and rear pump compartment enclosed by roller shutters. Custom stowage for items of fire fighting and rescue equipment.



### Equipment / Accessories

Emergency warning light bar.  
Repeater lamps front and rear.  
Emergency warning siren and PA system.  
Two-tone emergency warning horns.  
Spot lamp.  
Four lengths of suction hose with strainer.  
12 lengths of delivery hose.  
Four jet/spray water branch pipes.  
Four low expansion foam making branch pipes.  
Extension ladder.