



Angloco

Anglo 900 Compact Water/Foam Tender



OUTLINE SPECIFICATION

Chassis & Crew Cab

Iveco Cargo 80E15D chassis crew cab.
Engine: 143 bhp (105 kW).
Transmission: automatic gearbox.
GVW: 7,500 kg.
Crew cab with seating for 7 (driver + six).
Sit-and-strap BA brackets for four rear crew.

Fire Engineering

Water Tank 800 litres. Hot dip galvanised mild steel.

Foam Tank 100 litres. Plastic construction.

Water Pump Multi-pressure light alloy centrifugal pump, nominally rated at 2,500 litre/min @ 7 bar. High pressure output for the hose reels. Central suction connection. Two rear facing screw-down delivery valves. Automatic primer.

Hosereels Two manual rewind high pressure hose reels, one each side at the rear, each with 54m of 19mm hose, and jet/spray branch pipe.

Foam System Automatic around-the-pump foam system.

Bodywork Heavy duty aluminium construction, with full interfacing to protect against corrosion. Three lockers per side, plus rear pump bay, all enclosed by anodised aluminium roller shutter doors. Gantries for two ladders. Enclosed stowage for four lengths of suction hose. Rear access ladder. Sliding cradle for heavy equipment. Adjustable shelves.

Standard Accessories Full width emergency warning light bar. Electronic siren/PA system. Four repeater lamps. Automatic battery charger. Top-up brake air compressor. Pneumatic telescopic floodlight mast. Officer's spot lamp.

Finish Fully painted to customer's specification.

Options/Variations To meet individual customer requirements.

Full specifications available on request