



Angloco

Emergency Tender 4x4



OUTLINE SPECIFICATION

Chassis & Cab Mercedes-Benz Atego 1628AF 4x4.
279 hp (205 kW) turbocharged diesel engine.
Automatic transmission. 16,000 kg GVW.
Differential locks for front and rear axles.
Air conditioned crew cab for six persons.
Integrated SCBA stowage for four at the rear.

Installed Equipment

Hydraulic Crane Lifting capacity 3,400 kg at 2.4 m / 1,520 kg at 5.4 m; 406° slewing; maximum reach 5.7 m.
1,000 kg hydraulic hoist with 38 m x 8 mm wire rope, mounted under the outer boom.

Winch 5,000 kg hydraulic powered winch at the front, with 50 m x 13 mm wire rope.

Generator 20 kVA hydraulically-driven generator, 220 V, with protected outlet sockets and control panel.
3.5 kVA portable generator.

Lighting Telescopic mast extending 6 m above ground, with 2 x 1500 W flood lamps. Portable search/floodlighting, with tripod and cable reels.

Bodywork Specialist bodywork superstructure, with aluminium roller shutters enclosing upper compartments, and hinged doors for lower compartments forming steps when opened, providing access to central areas of the body. Custom shelving and specialist facilities to stow and carry rescue equipment.



Equipment / Accessories

Siren/PA system. Light bar. Repeater lamps. Mains battery charger. Set of hydraulic rescue equipment. Low pressure air lifting bags. Leak sealing air bags. High pressure air bags. Mobile air cart & respirators. SCBA sets. Confined space victim location system. Life detection seismic/acoustic listening devices. Pneumatic rescue line thrower. Thermal imaging cameras. Confined space rescue set, tripod & winch. Manual cable pull with wire rope. Support props. Concrete impact drill. Pneumatic impact rescue tool. Disc saw. Chain saw. Flame cutting equipment set. Hydraulic jacks. Electric ventilation fan. Telescopic ladders. Portable pump. Delivery hose. Branch pipes. Decontamination shower. Chemical protection suits. Stretcher. Manual rescue tools. Electrician's tools.