



# Angloco

## Heavy Rescue Tender 4x4



### OUTLINE SPECIFICATION

**Chassis & Cab** Scania P380CB4X4HHZ. 380 hp (279 kW) diesel engine. Automatic transmission. Automatic engine air inlet shut-down valve. Exhaust spark arrester. CP16 air conditioned cab with seating for two persons.

### Installed Equipment

**Hydraulic Crane** Lifting capacity 5,400 kg at 2.6 m / 760 kg at 15 m; 406° slewing; maximum reach 15.1m.

**Winch** 3,600 kg electric winch with 30 m cable.

**Generator** 20 kVA PTO-driven generator, 110 V, 50 Hz, CTE, protected outlet sockets, control panel.

**Lighting** Telescopic mast extends 7 m above ground, with 6 x high power flood lamps. Side and rear mounted scene lights. Portable lamps.

**Service Supply Reels** Five electric rewind reels, each with guide rollers, providing installed service supplies for rescue tools, accessories and equipment. 2 x hydraulic hose reel. 2 x electric cable reel. 1 x utility air hose reel.

**Bodywork** Aluminium construction with locker storage compartments enclosed by roller shutters, and fold-down steps providing access to central area of the body. Custom shelving and facilities to stow and carry rescue equipment. Electrically operated roof mounted awnings.



### Equipment / Accessories

Siren/PA system. Light bar and repeater lamps. Headlamp flasher. Reversing assistance sensor system and camera. Battery master switch. Mains powered battery charger and brake air compressor. Set of hydraulic rescue equipment including 2 x spreaders 2 x cutters, 5 x rams, 2 x pedal cutters, combi tool, portable power unit with 2 x 20 m hose reels, battery-pack power unit. Rescue platform. Set of pneumatic lifting bags. Reciprocating electric saws. Air powered cut-off tool. Manual rescue tools. Safety, protection and rescue equipment including stokes basket, spine boards, head immobiliser, rescue tripod and winch, rope lines, rescue stretcher, resuscitator. Extension ladder. Lifting slings. Portable winch.